



## NTN Bearing Driveshaft do Brasil



38,1 mm x 65,088 mm x 18,288 mm 38,1 mm x  
65,088 mm x 18,288 mm NTN 4T-  
LM29749/LM29710 tapered roller bearings

Bearing No. 4T-LM29749/LM29710

4T-LM29749/LM29710 Bearing 2D drawings and 3D  
CAD models

Size	38.1x65.088x18.034 mm
Bore Diameter	38,1 mm
Outer Diameter	65,088 mm
Width	18,034 mm
d	38,1 mm
D	65,088 mm
T	18,034 mm
B	18,288 mm
C	13,97 mm
d1	52 mm
a	13.73 mm
e	0.33
Y2	1.8
Y0	0.99
Mass	0.24 kg
Dynamic load, C	43.5 kN
Rating life coefficient, A2	1.4
Static load, C0	57 kN
Fatigue limit load, Cu	7 kN
Nlim (oil)	7,400 rpm
Nlim (grease)	5,500 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C



## NTN Bearing Driveshaft do Brasil

Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.22 Hz
Characteristic outer ring frequency, BPF0	9.27 Hz
Characteristic inner ring frequency, BRFI	11.73 Hz
ra max	2.3 mm
r1a max	1.3 mm
Category	Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.234
EAN	4547359481860
Product Group	B04334